

M A T E R I A L S A F E T Y D A T A S H E E T

DT-9500

Page: 1
7/3/2013



PRODUCT INFORMATION: WATER-BASED ADHESIVE
PRODUCT NAME: DT-9500

HMIS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: DriTac Flooring Products, LLC.
ADDRESS : 60 Webro Road
Clifton, NJ 07012

EMERGENCY PHONES

CHEMTREC 24 HOURS : 800-424-9300
CHEMTREC INTERNATIONAL : 703-527-3887 DATE PRINTED : 1/30/2013
INFORMATION PHONE : 1-973-614-9000 NAME OF PREPARER : R&D LAB

CHEMICAL FAMILY: WATERBORNE LATEX ADHESIVE

===== SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS =====

NATURAL LATEX AND SYNTHETIC RESINS PROPRIETARY MIXTURE 45 - 55%
WATER CAS # 7732-18-5 45 - 55%

===== SECTION III - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS CAS NUMBER VAPOR PRESSURE WEIGHT
 mm Hg @ TEMP PERCENT

*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION IV - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 212⁰F SPECIFIC GRAVITY (H2O=1): 1.45
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN N-BUTYL ACETATE

COATING V.O.C.: 0 g/l MATERIAL V.O.C.: 0 g/l
(VOC calculated per SCAQMD Rule 1168)

SOLUBILITY IN WATER: DISPERSIBLE
APPEARANCE AND ODOR: OFF-WHITE VISCOUSE LIQUID; MILD ODOR

===== SECTION V - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: ASTM D3828-07
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/APPL. UPPER: N/APPL.

THIS PRODUCT DOES NOT SUSTAIN BURNING ACCORDING TO ASTM D4206-96(01).

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

M A T E R I A L S A F E T Y D A T A S H E E T

DT-9500

Page: 1
7/3/2013

SPECIAL FIREFIGHTING PROCEDURES

WHEN DRIED MATERIAL BURNS, WATER (H2O), CARBON DIOXIDE (CO2), CARBON MONOXIDE (CO), AND SMOKE ARE PRODUCED. PYROLYSIS PRODUCTS MAY INCLUDE SOME HAZARDOUS MATERIAL. USE RECOMMENDED BREATHING APPARATUS FOR PROTECTION FROM SUCH HAZARDS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

THERE ARE NO UNUSUAL FIRE OR EXPLOSION HAZARDS.

===== SECTION VI - STABILITY AND REACTIVITY =====

STABILITY: STABLE

CONDITIONS TO AVOID

AVOID CONDITIONS WHERE CONTAMINATION WITH STRONG OXIDIZING AGENTS OR WATER SENSITIVE MATERIALS MAY OCCUR. SEE BELOW.

INCOMPATIBILITY (MATERIALS TO AVOID)

REACTS WITH STRONG OXIDIZING AGENTS AND ANY WATER SENSITIVE MATERIAL. EXERCISE CAUTION. READ MSDS POSTER FOR DETAILS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON DIOXIDE (CO2), AND CARBON MONOXIDE (CO).

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR N/A

===== SECTION VII - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INHALED, VAPORS MAY CAUSE RESPIRATORY IRRITATION, NAUSEA, HEADACHE. MOVE VICTIM TO FRESH AIR AND, IF BREATHING IS DIFFICULT, GET MEDICAL HELP.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE IRRITATION AND REDDENING. WASH SKIN THOROUGHLY WITH SOAP AND WATER. IF SPLASHED IN THE EYE, FLUSH WITH COPIOUS QUANTITIES OF WATER AND SEEK MEDICAL ADVICE.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

TO AVOID ANY POSSIBLE SKIN IRRITATION, IT IS DESIRABLE TO MINIMIZE SKIN CONTACT WITH THIS PRODUCT AS MUCH AS POSSIBLE BY WEARING APPROPRIATE PROTECTIVE CLOTHING, GLOVES, CHEMICAL SAFETY GOGGLES, ETC.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

TOXIC IF SWALLOWED. MAY CAUSE VOMITING, NAUSEA, DIARRHEA. THE MATERIAL WILL COAGULATE (SOLIDIFY) IN THE DIGESTIVE TRACT. SEEK IMMEDIATE MEDICAL ATTENTION.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

SKIN CONTACT MAY AGGRAVATE AN EXISTING ALLERGY, SUCH AS DERMATITIS. GET MEDICAL ADVICE ASAP.

===== SECTION VIII - FIRST AID PROCEDURES =====

WASH THE SKIN WITH SOAP AND WATER. IF SPLASHED IN THE EYE, FLUSH WITH COPIOUS AMOUNTS OF WATER AND SEEK MEDICAL HELP, IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. CONSULT A PHYSICIAN. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. CONSULT A PHYSICIAN IMMEDIATELY FOR ADVICE AND SUPERVISION OF FIRST AID PROCEDURES.

===== SECTION IX - ACCIDENTAL RELEASE MEASURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

CONTAIN SPILL. RECOVER AS MUCH AS POSSIBLE FOR REUSE. ABSORB REMAINDER WITH AN INERT MATERIAL. PLACE INTO CLOSED CONTAINER AND STORE IN A SAFE LOCATION FOR DISPOSAL. WASH SPILL AREA WITH SOAP AND WATER. USE CARE TO AVOID FALLS.

WASTE DISPOSAL METHOD

DISPOSE OF WASTE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. MOST STATES PROHIBIT DISPOSAL OF LIQUIDS IN LANDFILLS. POLYMER (SOLIDS) CAN BE SEPARATED FROM LIQUID LATEX THROUGH COAGULATION BY THE ADDITION OF 0.3% CALCIUM CHLORIDE. PLACE SOLIDS INTO A CONTAINER FOR DISPOSAL.

M A T E R I A L S A F E T Y D A T A S H E E T

DT-9500

Page: 1
7/3/2013

===== SECTION X - HANDLING AND STORAGE =====

OPEN CONTAINERS IN WELL VENTILATED AREA AWAY FROM SPARKS OR OPEN FLAME. PRODUCT CONTAINS A SMALL QUANTITY OF FLAMMABLE SOLVENT WHICH MAY COLLECT IN HEADSPACE OF THE CONTAINER. THIS VAPOR COULD FLASH MOMENTARILY IF IGNITED BUT THE LIQUID MATERIAL WILL NOT BURN. WEAR APPROPRIATE PROTECTIVE CLOTHING EQUIPMENT - SEE HMIS LABEL CODES AND MSDS POSTER GUIDE.

OTHER PRECAUTIONS

KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE. STORE ONLY IN WELL VENTILATED AREAS INDOORS AT TEMPERATURES NOT BELOW 50 DF. KEEP FROM FREEZING.

===== SECTION XI - EXPOSURE CONTROL/PERSONAL PROTECTION =====

RESPIRATORY PROTECTION

NONE RQUIRED.

VENTILATION

EFFECTIVE EXHAUST VENTILATION SHOULD ALWAYS BE PROVIDED TO DRAW MISTS, FUMES AND VAPORS AWAY FROM WORKERS TO PREVENT ROUTINE INHALATION.

PROTECTIVE GLOVES

RECOMMENDED.

EYE PROTECTION

WEAR SAFETY GOGGLES TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

N/A

WORK/HYGIENIC PRACTICES

SAFETY SHOWER, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE. WASH HANDS BEFORE EATING, DRINKING, ETC.

===== SECTION XII - TOXICOLOGICAL INFORMATION =====

HEALTH HAZARDS (ACUTE AND CHRONIC)

THE THRESHOLD LIMIT VALUE FOR THIS PRODUCT HAS NOT BEEN ESTABLISHED. NO ACUTE OR CHRONIC HEALTH HAZARDS REPORTED.

ACCUTE ORAL TOXICITY (LD50 RAT)

> 5000 mg/kg

ACCUTE DERMAL TOXICITY (LD50 RABBIT)

> 2000 mg/kg

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

===== SECTION XIII - ECOLOGICAL INFORMATION =====

POSSIBILITY OF ENVIRONMENTAL IMPACT:
NOT KNOWN

===== SECTION XIV - TRANSPORTATION INFORMATION =====

ACCORDING TO ASTM D4206-96 THIS PRODUCT DOES NOT SUSTAIN BURNING AND DOES NOT MEET THE DEFINITION OF ANY HAZARD CLASS.
DOT
NOT REGULATED AS DANGEROUS GOODS
IATA
NOT REGULATED AS DANGEROUS GOODS
IMDG
NOT REGULATED AS DANGEROUS GOODS

M A T E R I A L S A F E T Y D A T A S H E E T

DT-9500

Page: 1
7/3/2013

===== **SECTION XV - REGULATION INFORMATION**=====

FEDERAL REGULATIONS: All COMPONENTS ARE ON THE U.S. EPA TSCA IINVENTORY LIST..

THIS PRODUCT DOES NOT CONTAIN CHEMICALS SUBJECT TO THE REPORT REQUIREMENTS OF SARA SECTION 311/312 OF TITLE III.

THIS PRODUCT DOES NOT CONTAIN CHEMICALS SUBJECT TO THE REPORT REQUIREMENTS OF SARA SECTION 313 of Title III and of 40 CFR 372.

===== **SECTION XVI - OTHER INFORMATION**=====

DISCLAIMER

THE INFORMATION PROVIDED IN THIS MSDS HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, WE PROVIDE NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, AND WE ASSUME NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. IT IS THE USER'S RESPONSIBILITY TO SEE THAT THE DATA IS COMPLETE FOR HIS/HER PARTICULAR USE.