






FLOOR TYPE	DRITAC TROWEL	TROWEL DIAGRAM*
Vinyl Tile & Vinyl Plank (over porous substrates)	TR-8 1/16" x 1/16" x 1/16" Square notch Up to 200 sq. ft./gal. spread rate	
Vinyl Tile & Vinyl Plank (over non-porous substrates) Carpet Tile, Fiberglass Backed Sheet Vinyl	1/16" x 1/32" x 1/32" U notch 300 sq. ft./gal. spread rate	
Multi-Ply Engineered Plank	TR-2 3/16" x 1/4" x 1/2" V notch 60 sq. ft./gal. spread rate	
Cork Tile/Cork/Rubber /Foam Underlayment (up to 1/4")	TR-3 3/32" x 3/32" x 3/32" V notch 120 sq. ft./gal. spread rate	
Cork Tile/Cork/Rubber /Foam Underlayment (greater than 1/4")	TR-5 1/8" x 1/8" x 1/8" Square notch 80 sq. ft./gal. spread rate	
<p>* Diagrams not to scale. Use DriTac adhesives with a properly notched trowel. All square footage rates are estimated. Rates will vary based on substrate condition and the angle the trowel is held to the subfloor. DriTac Warranties do not cover problems caused by improper use of installation products. Follow flooring manufacturer's written installation instructions.</p>		