

Care, Maintenance & repair



Contents

Contents.....	1
General maintenance.....	2
Super hardwax.....	3
UV lacquered.....	5

To keep your floor in optimum condition we have the following guidelines to get the best out of your floor.

The installation instructions that came with the original packing are always to be observed first.

Depending on which appearance / product you have selected there are a number of guidelines on the maintenance. The following is applicable to all:



- 1) Use a good door mat at every entrance (inside and outside) and clean them often
- 2) Use soft protective pads for your table and chair legs (do not use a hard adhesive, it will scratch your floor)
- 3) Put a protective mat under chairs with wheels or replace wheels/casters with same suitable for wood flooring
- 4) Clean up any liquid spillages quickly. Remember that moisture should not come in contact with the floor. If it does, it should be wiped up immediately
- 5) Remove shoes with spikes or damaged heels before walking on the floor
- 6) Be aware that sunlight will intensify the colour of your floor, it is a natural process. If using area rugs in the house, make sure to move them periodically, to ensure the UV rays don't unevenly fade or change the color of the wood and/or stain
- 7) Keep your pet's nails clipped to reduce scratching of the floor.
- 8) Use daily a vacuum cleaner with attachment for wood floors or soft brush/broom which doesn't scratch. If required, wipe with a damp-dry (well squeezed) cloth.

To know how to maintain your floor, you shall assess which floor you have. See below table with the names of the products/finishes. It is not important whether you have a 14/15mm click floor or an 18/19/20mm structural floor.

Safety note:

All finished floors are safe for residential and in most cases for commercial applications, as long as the maintenance & instructions are observed. Separately its important to notice that the surface of the flooring shall at all times be dry, or it will become slippery. In circumstances that the surface has spillages, additional precautions have to be taken to prevent slipperiness. Consult your flooring dealer for details on possible remedies.

Never use a wax finish on top of a UV lacquered surface finish. Use a cleaner specifically designed for use on polyurethane finished floor.

Super hardwax

The floor is finished with a hardwax oil that is based on a molecular bonding technology using natural ingredients to bind with the top part of the wood fibers of the flooring. This signature technology ensures that these ecological products are warm & natural in appearance



- A Pure finish HPPC
- B Walnut Finish HPPC
- C Lightly fumed, Brushed, HPPC White
- D Black HPPC Finish Distressed
- I Distressed & Wenge Stained, HPPC Pure
- R White HPPC Finish
- W Colonial HPPC
- BB 2 coats of HPPC Walnut
- AF Colonial HPPC on normal Ukraine Oak
- AN Edge & Surface distressed, HPPC Colonial
- AP Brushed & White Hardwax
- BC Edge & Surface distressed, Charcoal HPPC
- BD Edge & Surface distressed, Walnut HPPC
- BE Edge & Surface distressed, Raw Invisible
- BG SkyGray
- BH Brushed & Titanium Gray
- BI Heavy Brushed, Fumed Clay, no white ceruse
- BJ Heavy Brushed, Fumed Clay, whitewash, LOW GLOSS
- CH Brushed & Charcoal HPPC
- BK Vintage, light brush & edge distr, Invisible HPPC

Daily Care & Maintenance

- 1) Daily cleaning with vacuum cleaner and moist, but not wet MOB as too much humidity makes wood swell and it will create problems.
- 2) Weekly floor cleaning with Rubio MonoCoat Soap.
- 3) Don't clean the floor first 3 weeks after installation. Just clean it with a dry cloth.

Monthly Care & Maintenance

Periodic cleaning with Rubio MonoCoat cleaner.

Repair & Surface finish renovation

1. Once a year use, depending on the intensity of the traffic, to clean the floor and use Rubio Mono-Coat 2C Plus (RMC 2C Plus) oil in the correct colour to totally refresh the floor.
 - 1) If something heavy drops on the floor or surface and it is damaged, it can be repaired as well, by sanding the damaged area and apply the RMC 2C Plus. Leave to dry. Observe the instructions on the tin.
 - 2) RMC Surface Care spray is available to repair localized areas.

UV lacquered

Prefinished lacquered floors have a hard-wearing factory applied polyurethane lacquer surface. The life span of the lacquered surface largely depends on proper cleaning and maintenance. However, in high-traffic areas, areas subject to spillages of liquids and floors subject to a high degree of maintenance, consideration should be given to a further coat of lacquer.

Daily Care & Maintenance

Daily cleaning with vacuum cleaner to remove dust and grit and use moist, but not wet mop as too much humidity makes wood swell and it will create problems.

Monthly Care & Maintenance



Clean the floor with generic Lacquer refresher (revival liquid).
Check www.DuraSeal.com for these maintenance products and local distributor.
Intervals between treatments depend on the degree of traffic.

Repair & Surface finish renovation

Remove old grease, dirt, and sand the floor.
Staining and relacquering.
Consult www.Duraseal.com and find your preferred colour. Instructions are on the site to show how it should be done.