

*Sound***TERMINATOR**

Sound Terminator
For use as underlayment for Laminate and floating wood floor installation

Virgin-Recycled HD Rubber /Foam
LEED benefits
IIC=60 STC= 54
Warrantied for the lifetime of the floor
Residential & Commercial applications
Superior Sound Deadening
Water Resistent
Fire Retardant, Code Compliant
Mold & mildew resistant
Lays flat, easy to install



ADVANTAGES

- 24.5 HD dense foam/rubber control mat
- Superior sound deadening
- Excellent crack suppressant
- Guaranteed to never color leach
- Available in any thickness or length - 4ft. wide
- Easily cut in place
- Can be loose laid
- Closed cell production to prevent flattening
- Adhesive can be easily applied without tearing
- LEED points
- High thermal insulation
- Antimicrobial to prevent mold, mildew and bacteria

TECHNICAL DATA

Sample ID.....	Sound Terminator pcf Foam
Durometer, Shore A (ASTM D2240).....	.50
Thickness (in.).....	0.12
Density, pcf (ASTM D792).....	.59
Density, g/cm2 (ASTM D792).....	0.95
Tensile, psi (ASTM D412 Die C).....	.95
Elongation, % (ASTM D412 Die C).....	.75
Tear, pli (ASTM D624 Die C).....	.43
Compression (100 psi, ASTM F36, procedure F).....	18.2%
Recovery (100 psi, ASTM F36, procedure F).....	84.1%
Compression Set (25% deflection 22 hrs@158oF, ASTM D395).....	51.0%

