



MAINTENANCE & CARE

SANDY MOUNTAIN, LOWLANDS COLLECTIONS

General

- Lansfield Flooring Collection Luxury Vinyl Tile does not require a floor finish for protection or to maintain their appearance. However, the use of a finish is acceptable in order to obtain a higher luster.
- Do not at any time flood the floor either at initial maintenance or anytime thereafter.
- Maintenance products:
 - Regular neutral cleaner/degreaser (7 to 7.5 pH before dilution).
 - Low foam neutral cleaner for auto scrubber (7 to 8 pH before dilution).

Initial Maintenance

- For Sandy Mountain & Lowlands make sure the adhesive is fully cured before starting (refer to installation instructions - minimum of 48 hours after installation).
- Start by removing foreign particles such as soil, sand, dust or grit. This can be done by sweeping, vacuuming or dust mopping.
- Damp mop using a low foam neutral resilient flooring cleaner being careful to not “flood” the floor as excessive amounts of water can cause adhesive to break down and release.
- Use a wet vacuum or a mop to remove excess water and residue. Be sure to let the floor dry completely.

Regular Maintenance

- Sweep or vacuum daily to remove dust and dirt. If necessary clean with a wet mop using a neutral cleaner/degreaser.

Preventive Maintenance

- Use of proper floor protection is important to maintain the beauty of Lansfield Flooring Collection floor. It is recommended to use plastic castors and glides of adequate size. Be sure they are cleaned on a regular basis as dirt and grit can accumulate on the bottom.
- Constant exposure to direct sunlight can result in tiles shrinking or fading. The use of blinds during peak sunlight hours is recommended.



MAINTENANCE & CARE

SANDY MOUNTAIN, LOWLANDS COLLECTIONS

- The use of walk-off mats is recommended in entranceways. Some types of walk-off mats may have a rubber backing that can cause the floor to discolor. Always make sure that the mat/rug supplier confirms they have a non-staining back.